

ANTI-STATIC SHOTBLAST HOSE, TYPE 2K / ABRAZIJA-PESKIRANJE

HOSE SIZE VELIČINA CREVA		INSIDE DIAMETER		REINFORCEMENT DIAMETER		OUTSIDE DIAMETER		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT		CODE/ŠIFRA
		mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft	
DN	dash															
16		16	5/8"			30	1,181	20	290	60	870	110	4,331	600	0,407	AB-020-016
19		19	3/4"			33	1,299	20	290	60	870	130	5,118	640	0,430	AB-020-019
22		22	7/8"			36	1,417	20	290	60	870	150	5,905	745	0,500	AB-020-022
25		25	1"			41	1,614	20	290	60	870	160	6,299	965	0,648	AB-020-025
28		28	1-1/8"			44	1,732	20	290	60	870	180	7,087	1050	0,705	AB-020-028
31		30	5/4"			46	1,811	20	290	60	870	200	7,870	1085	0,728	AB-020-031
35		35	1-3/8"			50	1,969	20	290	60	870	220	8,661	1155	0,775	AB-020-035
38		38	1-1/2"			53	2,087	20	290	60	870	250	9,843	1250	0,839	AB-020-038
40		40	1-9/16"			55	2,165	20	290	60	870	290	11,417	1300	0,872	AB-020-040
50		50	2"			68	2,677	20	290	60	870	350	13,779	1980	1,328	AB-020-050
63		63	2-1/2"			81	3,188	20	290	60	870	420	16,535	2450	1,643	AB-020-063

Customer can choose other: diameter, pressure and color / Po zahtevu kupca mogu se izraditi drugi: prečnici, pritisak creva i boje.

INFO:

TUBE - NR/BR rubber abrasion resistance to DIN 53516

REINFORCEMENT - Multiple textile plies.

COVER - Environment resistant synthetic rubber.

MAIN APPLICATIONS TYPES

For sandblast device and abrasive materials.

RECOMMENDED FLUIDS

The hoses are intended for flow of various pulverized granular and solid abrasive materials, or solids fluidized in liquid or air, for sand, cement, gravel, concrete, for different ores, for fertilizers and other chemical products. Besides, these hoses are used for devices for sand blasting and finishing (cleaning of metal, glass, stone and similar surfaces).

FEATURE - Very long service life due to abrasion resistant tube wear of the tube less than 50mm³

APPLICABLE SPECS: EN ISO 3861:1997; BS 5121

CONTINUOUS SERVICE: -30°C / +80°C

MAX OPERATING TEMPERATURE: +100°C

INFO:

DONJA GUMA - NR/SRB/BR abrazivna guma po DIN 53516.

OJAČANJE - Tekstilni oplit po potrebi.

OBLOGA - Kvalitetna sintetička guma.

PRIMENA - Za abrazivne materijale.

PREPORUČUJEMO

Koristiti za zrnaste i čvrste abrazivne materijale, pesak, cement, šljunak, beton, razne rude, mineralna đubriva... Ova creva se koriste na mašinama za peskiranje i doradu (čišćenje metala, stakla, kamena i sličnih površina).

ISTIČEMO - Creva imaju veoma dug vek trajnosti zbog gume abrazivnosti ispod 50mm³

STANDARD: EN ISO 3861:1997; BS 5121

TEMPERATURNI OPSEG: -30°C / +80°C

MAKSIMALNA TEMPERATURA: +100°C

